

LED Linear Strip #21020 & #21025

3-Wattages + 3-CCT (35/40/50K), Damp Rated, Up to 135 lm/W, Dimmable + Smart

FEATURES

Lumen Output	3120 to 10800 lumens
Efficacy	Up to 135 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
Size	4-FT, 8-FT
CCT	Select (3500K, 4000K, 5000K)
Rating	Damp Location
Warranty	7 Years

APPLICATIONS

Premium indoor luminaire for hanging or surface mounting in ceiling spaces less than 25 feet. Suitable for gymnasiums, warehouses, manufacturing, packaging, storage, aisles, work-stations, and covered decks.

CONSTRUCTION

Manufactured for durability using aluminum sheet housing with semi-gloss coating to resist corrosion, discoloration, and scratching. Damp Location rated.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3500K, 4000K, 5000K) and Tunable 3-Wattages. Operating temperatures -4°F to 104°F (-20°C to 40°C).

MOUNTING

Surface mounting standard. Optional 10-FT Aircraft Cables for hanging available.

OPTICS

Anti-UV Frosted Polycarbonate Lens standard.

CONTROLS

Installed fixture mounted Microwave Sensor, PIR Sensor or Bluetooth with Daylight Priority available. Remote Control available.

EMERGENCY

Installed 90 Minute Emergency Backup Battery LED Driver options available.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

5 year exclusive limited warranty.

Project:
Date:
Catalog No:
Prepared By:

4-FT Low Bay, and 8-FT High Bay Models



PIR Sensor or Bluetooth



Microwave Sensor



Remote Control



LCD Remote Control




Emergency Driver



TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3500K



4000K



5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V
Input Frequency: 50/60 Hz
Wattage: 3-Wattages (40W Max, 80W Max)
Power Factor: >0.9
Total Harmonic Distortion (THD): <10%
Operating Temperature: -4°F to 104°F (-20°C to 40°C)

LIGHTING DATA

Lumens: 3120 to 10800
Lumens Per Watt: Up to 135 lm/W
Correlated Color Temperature (CCT): 3-CCT (35K, 40K, 50K)
Dimmable: 0-10V
Color Rendering Index (CRI): >80
L70: 75000 hours

ORDERING INFORMATION

Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
#21020	4-FT	(24W, 32W, 40W)	120-277V	0.22A@120V, 0.10A@277V 0.29A@120V, 0.13A@277V 0.37A@120V, 0.16A@277V	3120 4160 5200	130 lm/W	(3500K, 4000K, 5000K)	0-10V	White	46.65"L x 2.91"W x 3.27"H
#21025	8-FT	(60W, 70W, 80W)	120-277V	0.55A@120V, 0.24A@277V 0.64A@120V, 0.28A@277V 0.73A@120V, 0.32A@277V	8100 9450 10800	135 lm/W	(3500K, 4000K, 5000K)	0-10V	White	95.98"L x 2.91"W x 3.27"H

Mount	Control	Emergency
ST0-CN One Daisy Chain Connector	US008-016VCR [INSTALLED] Microwave Sensor with Daylight Priority and Daylight Harvesting, DC12V	EM6 INSTALLED - Emergency LED Driver, 6W, 90-Minute Battery
TLS-ACKIT Pair of 10-FT Aircraft Hanging Cables		EM15 INSTALLED - Emergency LED Driver, 15W, 90-Minute Battery
(Blank) None, for Surface Mounting	HD08VR-1 [INSTALLED] PIR Sensor with Daylight Priority and Daylight Harvesting, AUX Input	EM20 INSTALLED - Emergency LED Driver, 20W, 90-Minute Battery
	HD08VR-MB-1 [INSTALLED] PIR Sensor with Daylight Priority and Daylight Harvesting, AUX Input (Bluetooth)	EM25 INSTALLED - Emergency LED Driver, 25W, 90-Minute Battery
	HD03R Remote Control for Sensor Settings	
	HD05R Remote Control for Sensor Settings w/ LCD	
	SD250 [INSTALLED] Step-Down Autotransformer 480V to 277V, Up To 250W	

PHYSICAL DIMENSIONS

4-FT Models

46.65"L x 2.91"W x 3.27"H

8-FT Models

95.98"L x 2.91"W x 3.27"H

