

TriLum Tunable

LED Full Cutoff Wall Pack

3-Wattages + 3-CCT (30/40/50K), Wet Rated, 130 lm/W, Dimmable + Photocell

FEATURES

Lumen Output	5200 to 15600 lumens
Efficacy	130 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	Select (3000K, 4000K, 5000K)
Rating	Wet Location
Warranty	5 Years

APPLICATIONS

Premium outdoor luminaire suitable for wall mounting on building exteriors for entrances, courtyards, alleys, and pedestrian walkways. Dark Sky Friendly.

CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. Wet Location rated.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3000K, 4000K, 5000K) and Tunable 3-Wattages. Operating temperatures -4°F to 113°F (-20°C to 45°C).

MOUNTING

Wall mounted installations.

OPTICS

Anti-UV Clear Polycarbonate Lens.

CONTROLS

Includes fixture integrated Photocell sensor.

LISTINGS

UL listed, FCC & RoHS compliant.

WARRANTY

5 year exclusive limited warranty.

Project:
Date:
Catalog No:
Prepared By:

Dark Sky Friendly Tunable Models include Photocell Sensor





TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3000K

4000K

5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V
Input Frequency: 50/60 Hz
Wattage: 3-Wattages (80W Max, 100W Max, 120W Max)
Power Factor: >0.9
Total Harmonic Distortion (THD): <20%
Operating Temperature: -4°F to 113°F (-20°C to 45°C)

LIGHTING DATA

Lumens: 5200 to 15600
Lumens Per Watt: 130 lm/W
Correlated Color Temperature (CCT): 3-CCT (30K, 40K, 50K)
Dimmable: 0-10V
Color Rendering Index (CRI): >70
L70: 50000 hours

ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
51106	(40W	120-277V	0.37A@120V, 0.16A@277V	5200	130 lm/W	(3000K,	0-10V	Bronze	14.24"L x 6.60"W x 9.27"H
	60W		0.55A@120V, 0.24A@277V	7800		4000K,			
	80W)		0.73A@120V, 0.32A@277V	10400		5000K)			
51108	(80W	120-277V	0.73A@120V, 0.32A@277V	10400	130 lm/W	(3000K,	0-10V	Bronze	14.24"L x 6.60"W x 9.27"H
	100W		0.92A@120V, 0.40A@277V	13000		4000K,			
	120W)		1.10A@120V, 0.48A@277V	15600		5000K)			

PHYSICAL DIMENSIONS

All Models

14.24"L x 6.60"W x 9.27"H

